

SX-19



▶ FEATURES

- High 1280 x 1024 SXGA resolution
- Looping video inputs for multiple connections
- Auto termination
- Quick signal-switching time
- Supports color and B/W picture
- NTSC/PAL/SECAM scan system compatible
- Selectable signal source
- PC compatible
- Auto-adjustment for optimal setting
- NeoV Optical Glass™
- Distinctive aluminum alloy housing for added strength
- Kensington® security socket
- VESA standard wall mount

▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	19" (483mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294mm
	Brightness	300cd/m ² (Typical)
	Contrast Ratio	700:1 (Typical)
	Viewing Angle (H/V)	150°/130° (Typical)
	Display Color	16.7M
	Response Time	4ms (GTG)
	Frequency (H/V)	H: 30kHz - 80kHz V: 50Hz - 75Hz
Input Connector	Max. Pixel Clock	135MHz
	Life Time	50,000hrs (Typical)
	Analog	15-Pin D-Sub
Input Signal	Digital	29-Pin DVI-D
	BNC Security	BNC Connector
	Auto Composite System	NTSC/PAL/SECAM
Output Connector	BNC Security	BNC Connector
	Thickness	3.0mm (0.18")
NeoV Optical Glass	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	Tilt	0° ~ +15°
Mounting	VESA FPMPI	Yes (100mm)
Regulation Approval	Certifications & Compliance	FCC, UL/CUL, TUV/BAURT, CE, BSMI, ISO 13406-2, GOST, WEEE, RoHS
	VESA	DDC 1/2B, DPMS
Power	Power Source	100 - 245V, 50 - 60Hz
	Consumption	<48W (On) <4W (Stand-by) <2W (Off)
	Operation	0°C ~ 40°C
Dimensions	Net (W x H x D)	444 x 419 x 175mm (17.5" x 16.5" x 6.9")
	Packing (W x H x D)	540 x 525 x 228mm (21.2" x 20.7" x 9.0")
Weight	Net Weight	7.9Kg (17.4lbs)
	Gross Weight	10.7Kg (23.6lbs)
Packing	1 Pallet	40 Cartons
	20' Container	400 Sets
	40' Container	880 Sets

All specifications are subject to change without prior notice

