

Portable SDI to HDMI converter

S-4600



Introduction:

The S-4600 is a portable 3G/HD/SD-SDI to HDMI converter. It converts the SDI with its embedded audio to HDMI output, and supports SDI loop through output and SDI embedded audio via 3.5mm earphone output. The S-4600 is heavy duty housing design, protecting the BNC connectors well, and supplied various screw threads in the bottom, for convenient installing, and future accessories (battery mount, etc)

Features:

- ◆ Portable 3G/HD/SD-SDI to HDMI Converter
- ◆ 1 SDI input, 1 HDMI output, and 1 SDI loop through output
- ◆ 1 analog audio (3.5mm) output
- ◆ Embed SDI audio to HDMI output
- ◆ SDI audio output via 3.5mm earphone socket
- ◆ Power/input/output status indicator
- ◆ Heavy duty housing
- ◆ Bottom screw threads for installing

Portable HDMI to SDI converter

S-4601



Introduction:

The S-4601 is a portable HDMI to 3G/HD/SD-SDI converter. It supports HDMI audio embedded into SDI output, and analog audio (3.5mm socket) input, embedded into SDI output.

The S-4601 is heavy duty housing design, protecting the BNC connectors well, and supplied various screw threads in the bottom, for convenient installing, and future accessories (battery mount, etc)

Features:

- ◆ Portable HDMI to 3G/HD/SD-SDI Converter
- ◆ 1 HDMI input, 2 SDI output,
- ◆ 1 analog audio (3.5mm) input
- ◆ Embed HDMI audio to SDI output
- ◆ Embed analog audio (3.5mm) to SDI output
- ◆ Power/input/output status indicator
- ◆ Heavy duty housing
- ◆ Bottom screw threads for installing

Specifications:

Model		S-4600	S-4601	
Input		3G/HD/SD-SDI×1	HDMI×1	
			Analog audio×1	
Output		3G/HD/SD-SDI×1	3G/HD/SD-SDI×2	
		HDMI×1		
		Earphonex1		
Format	SDI	SMPTE-425M	1080p(60, 59.94, 50)	1080p(60, 59.94, 50)
		SMPTE-274M	1080i (60, 59.94, 50)	1080i (60, 59.94, 50)
			1080p (30, 29.97, 25, 24, 23.98)	1080p (30, 29.97, 25, 24, 23.98)
		SMPTE-296M	720p (60, 59.94, 50)	720p (60, 59.94, 50)
		SMPTE-125M	480i (59.94)	480i (59.94)
	ITU-R BT.656	576i (50)	576i (50)	
	HDMI		1080p(60, 59.94, 50, 30, 29.97, 25, 24, 23.98)	1080p(60, 59.94, 50, 30, 29.97, 25, 24, 23.98)
			1080i (60, 59.94, 50)	1080i (60, 59.94, 50)
			720p (60, 59.94, 50)	720p (60, 59.94, 50)
			480i, 576i	480i, 576i
General	Power consumption	≤ 3W	≤ 3W	
	Working voltage	DC 12V	DC 12V	
	Working environment	0° - +70°temperature, 10%-90% humidity		
	Dimension	73×74.3×29 mm	73×74.3×29 mm	

SWIT Electronics Co., Ltd.

Website: www.swit.cc
 Email: contact@swit.cc
 Tel: +86 25 85805753
 Fax: +86 25 85805296

Distributed by:

